

Conveyor Belt Weighing

A practical guide to conveyor belt weighing, covering the reader intent, the relationship to conveyor belt weighing, key evaluation criteria, common risks, and the information the intended project audience should confirm before taking the next step.



levelmeter.org
Main topic: Main Page
<https://www.level-meters.com/>

In the landscape of industrial bulk material handling, the ability to accurately quantify the flow of solids is fundamental to operational efficiency, process control, and inventory management. Conveyor belt weighing, primarily achieved through the integration of belt scales, provides a continuous measurement of the mass flow rate and totalized weight of materials as they move along a conveyor system. Whether handling minerals in a mining operation, grain in agricultural processing, or chemicals in a manufacturing plant, understanding the mechanics and application of belt weighing is essential for modern automation.

While conveyor belt weighing focuses on the dynamic flow of material, it is inextricably linked to static storage monitoring. For a comprehensive overview of how these technologies integrate into broader industrial systems, engineers often refer to the Main Page of instrumentation providers to align flow data with vessel level data.

| Measurement Principles of Conveyor Belt Weighing

Conveyor belt weighing is not a single-sensor measurement but rather a system-level calculation derived from two primary variables: weight and speed. To determine the mass flow rate (typically expressed in kilograms per hour or tonnes per hour), the system must simultaneously measure the load on a specific section of the belt and the velocity at which that belt is moving.

| The Load Measurement (Weight)

The core of a belt scale is the weighbridge. This structure is installed under the conveyor belt, replacing one or more standard idlers. The weighbridge is supported by high-precision load cells, usually of the strain-gauge variety. As material passes over the weighbridge, the gravitational force exerted by the material is transmitted to the load cells. This force is converted into an electrical signal proportional to the weight per unit length (e.g., kg/m).

| The Speed Measurement (Velocity)

Because conveyor belts are subject to stretching, slipping, and variations in motor load, assuming a constant speed is often insufficient for high-accuracy applications. A speed sensor, typically a digital encoder or a friction-driven wheel, is mounted on the return belt or a non-driven pulley. This sensor provides a pulse frequency that corresponds to the belt's travel speed (m/s).

| The Integration Process

The signals from the load cells and the speed sensor are sent to an electronic integrator. The integrator performs the fundamental calculation:

$$\text{Mass Flow Rate (Q)} = \text{Load (L)} \times \text{Speed (V)}$$

By integrating this flow rate over time, the system provides a totalized weight of the material moved during a specific shift, batch, or day.

| Integration with Level Measurement Systems

In a typical industrial workflow, conveyor belt weighing does not exist in isolation. It is usually part of a closed-loop system involving storage silos, hoppers, and feeders. For instance, a radar level meter installed on a primary storage silo monitors the available inventory. When the level reaches a specific set point, the conveyor system is activated to transport material to a secondary process hopper.

Effective process automation requires that the data from the conveyor belt weighing system matches the volumetric changes reported by level sensors. If a belt scale reports that 50 tonnes of material have been moved, but the ultrasonic level sensor in the receiving bin indicates a volume change equivalent to only 40 tonnes, it signals a potential calibration issue or material loss. Manufacturers like Welk provide the level measurement side of this equation, ensuring that the static inventory data is as reliable as the dynamic flow data found on the Main Page.

| Selection Criteria for Belt Weighing Systems

Selecting the appropriate conveyor belt weighing system requires a detailed analysis of the conveyor's physical characteristics and the required accuracy of the data. Not all conveyors are suitable for high-precision weighing, and environmental factors play a significant role.

| Key Evaluation Factors

- 1. Required Accuracy: Commercial "legal-for-trade" applications require high precision (0.125% to 0.25% error), whereas simple process monitoring might only require 0.5% to 1.0% accuracy.
- 2. Belt Speed: High-speed belts (above 3 m/s) introduce more vibration and require more robust weighbridges and faster integration electronics.
- 3. Material Characteristics: The density, moisture content, and particle size of the material affect how it settles on the belt, which in turn affects the stability of the weight reading.
- 4. Conveyor Incline: While belt scales can operate on inclined conveyors, the angle must remain constant. Changes in the angle of the conveyor will change the force vector applied to the load cells, leading to errors if not properly compensated.

| Selection Table: Belt Scale Configurations

Feature	Single-Idler Scale	Multi-Idler Scale (2-4 Idlers)	Dual-Belt / Weighfeeder
Typical Accuracy	0.5% to 1.0%	0.125% to 0.5%	0.25% to 0.5%
Space Required	Minimal (one idler space)	Significant (2-5 meters)	Standalone unit
Primary Use	Process control, inventory	Trade loading, high-value bulk	Controlled dosing/blending
Maintenance	Low	Moderate	High
Cost	Economical	Premium	High

| Installation Considerations and Best Practices

The accuracy of a conveyor belt weighing system is often more dependent on the quality of the installation than on the electronics themselves. Because the system is measuring relatively small changes in force on a massive, moving structure, mechanical interference must be minimized.

| Location on the Conveyor

The weighbridge should be installed in a section of the conveyor where belt tension is most stable and consistent. This is typically at least 6 to 12 meters (or five idler spaces) away from the loading point to allow the material to settle. It should also be located away from curves, trippers, or any device that changes the belt's profile.

| Idler Alignment

The "scale area" includes the weigh idlers and at least two idlers before and after the scale. These idlers must be perfectly aligned in both the horizontal and vertical planes. If the scale idler is even a few millimeters higher than the adjacent idlers, it will take on more of the belt's tension, resulting in an artificially high weight reading.

| Belt Tensioning

Constant belt tension is critical. Gravity-take-up systems (using a counterweight) are preferred over screw-take-up systems because they automatically adjust for belt stretch and temperature fluctuations, maintaining a consistent tension across the weighbridge.

| Limitations and Environmental Challenges

Engineers must be aware of the physical limitations that can degrade the performance of conveyor belt weighing systems.

Wind Loading: On outdoor conveyors, wind can exert downward or upward pressure on the belt, which the load cells interpret as material weight. Wind shields are often necessary for accurate outdoor weighing.

Moisture and Material Buildup: If material sticks to the belt (carry-back), the system will totalize this weight repeatedly. Belt scrapers and an automatic zero-tracking function in the integrator are required to mitigate this.

Vibration: Nearby heavy machinery (crushers, screens) can transmit vibrations through the conveyor structure. Modern integrators use digital filtering to move past this noise, but mechanical isolation is always the first line of defense.

Belt Stiffness: At low temperatures, rubber belts become stiffer, which increases the resistance to bending over the scale idlers. This change in mechanical resistance can affect the zero-point calibration.

| Calibration Procedures

A belt scale is only as good as its last calibration. Because the system is dynamic, it requires periodic verification against known weights.

1. **Zero Calibration:** This is performed with the belt running empty. The system records the weight of the belt itself over one or more complete revolutions and averages it to establish a "zero" baseline.

2. **Static Weight Calibration:** Known weights are applied to the weighbridge while the belt is stationary. This tests the load cell response but does not account for dynamic belt effects.

3. **Electronic Calibration (R-Cal):** A resistor is used to simulate a load on the cells. This is useful for checking the health of the electronics but does not calibrate the mechanical system.

4. **Material Test:** The gold standard of calibration. A known quantity of material is run across the scale and then weighed on a static, certified platform scale. The belt scale's span is then adjusted to match the static weight.

| Frequently Asked Questions (FAQs)

Q: How often should a conveyor belt weighing system be calibrated?

A: For process control, a monthly zero calibration and a quarterly span check are usually sufficient. For high-accuracy or trade-certified systems, weekly zero checks and monthly material tests may be required.

Q: Can I weigh material on a reversible conveyor?

A: Yes, but it requires a more complex setup. The speed sensor must be able to detect direction, and the weighbridge must be positioned in a location that remains stable regardless of which end is the "head" pulley.

Q: Does belt weighing work for very light materials?

A: It is challenging. For very light materials (like sawdust or light plastics), the signal-to-noise ratio is low. In these cases, a weighfeeder or a specialized low-capacity belt scale with highly sensitive load cells is necessary.

Q: How do I choose between a belt scale and a level sensor for inventory?

A: They serve different purposes. A belt scale measures what is moving (throughput), while a level sensor (such as those found on the [Main Page](#)) measures what is stored (inventory). For full process transparency, both are typically required.

| Conclusion

Conveyor belt weighing is a sophisticated blend of mechanical engineering and digital signal processing. By understanding the principles of load and speed integration, and by adhering to strict installation and calibration standards, industrial facilities can achieve high levels of accuracy in their bulk material handling. When combined with reliable level measurement instruments to monitor storage vessels, belt weighing provides the data necessary for optimized production, reduced waste, and improved profitability in the global supply chain.